



Holosun 507K X2

Power ON: Shake sight or press either brightness button
Power OFF: Press "+" and "-" simultaneously to turn power and motion sensor off (**Shake Awake™** (*) is disabled)
 Press "-" 3 sec, to switch from Circle+Dot(*), Dot, and Circle
 Press "+" 3 sec, to switch from Manual (*) to Lockout Mode
 There are 10 daylight and 2 NV brightness settings.

*default

Layout / Design llando88@gmail.com 2022. Unlimited copy and distribution permitted. **REV 10**

GENERAL PURPOSE GRID: 1.00"

Holosun 507K X2



Battery is **CR1632**. Reticle blinks when battery is 2.2 V.
 Insert new battery "+" side down
Screws move center of impact U/D, R/L. **1 click = 1 MOA**
25 yds: 32 MOA = 8.4" 2 MOA = 0.5"
10 yds: 32 MOA = 3.4" 2 MOA = 0.2"
 Screws: Optic: 15 in lbs (blue loctite) Battery Tray: 6 in lbs
 Clean with lens cleaner, **NO** alcohol or acetone
 Footprint: Shield / Body AI 7075 / IP67 Certified

www.holosun.com warranty@holosun.com (909) 594-2888

Instructions: Cut on dotted lines / fold to make a 3x5 "card". Information adapted from OEM sources; not verified nor endorsed. User is advised to verify any content herein with manufacturers documentation.

ZEROING AID GRID: 2 MOA@25 YD=0.52"



Holosun 507K X2

Power ON: Shake sight or press either brightness button
Power OFF: Press "+" and "-" simultaneously to turn power and motion sensor off (**Shake Awake™** (*) is disabled)
 Press "-" 3 sec, to switch from Circle+Dot(*), Dot, and Circle
 Press "+" 3 sec, to switch from Manual (*) to Lockout Mode
 There are 10 daylight and 2 NV brightness settings.

*default

Layout / Design llando88@gmail.com 2022. Unlimited copy and distribution permitted. **REV 10**

GENERAL PURPOSE GRID: 1.00"

Holosun 507K X2



Battery is **CR1632**. Reticle blinks when battery is 2.2 V.
 Insert new battery "+" side down
Screws move center of impact U/D, R/L. **1 click = 1 MOA**
25 yds: 32 MOA = 8.4" 2 MOA = 0.5"
10 yds: 32 MOA = 3.4" 2 MOA = 0.2"
 Screws: Optic: 15 in lbs (blue loctite) Battery Tray: 6 in lbs
 Clean with lens cleaner, **NO** alcohol or acetone
 Footprint: Shield / Body AI 7075 / IP67 Certified

www.holosun.com warranty@holosun.com (909) 594-2888

Instructions: Cut on dotted lines / fold to make a 3x5 "card". Information adapted from OEM sources; not verified nor endorsed. User is advised to verify any content herein with manufacturers documentation.

ZEROING AID GRID: 2 MOA@25 YD=0.52"