

Leupold DeltaPoint® Pro

Power ON: Press and release power button

Power OFF: Press power button for more than 3 sec

Cycle through **8 illumination settings** using the power button.

When highest or lowest setting is reached, LED flashes 5 times. To change direction, hold the power button for 2 sec and immediately release.

Motion Sensor Technology™: Sight sleeps after 5 minutes. Any movement powers up sight to last setting.

Copyright © 2018 Leupold & Stevens, Inc. All rights reserved.

Layout / Design llando88@gmail.com 2022. Unlimited copy and distribution permitted. **REV 10**

GENERAL PURPOSE GRID: 1.00"

Leupold DeltaPoint® Pro



2.5 MOA DOT

Battery is **CR2032**. Aiming point flashes 10 times when low battery power is detected.

Open battery cover by pulling back the battery door release latch. Insert battery positive side (+) up.

Screws move point of impact U/D L/R 1 MOA per click

25 yds: 2.5 MOA=0.7" **10 yds:** 2.5 MOA=0.3"

Torque Optic Screws to 25 in-lbs.


Footprint: DeltaPoint Pro / Body Aluminum / Waterproof to 33'

productspecialist@leupold.com www.leupold.com (503) 526-1400

Copyright © 2018 Leupold & Stevens, Inc. All rights reserved.

Instructions: Cut on dotted lines / fold to make a 3x5 "card". Information adapted from OEM sources; not verified nor endorsed. User is advised to verify any content herein with manufacturers documentation.

ZEROING AID GRID: 2.5 MOA@25 YD=0.65"



Leupold DeltaPoint® Pro

Power ON: Press and release power button

Power OFF: Press power button for more than 3 sec

Cycle through **8 illumination settings** using the power button.

When highest or lowest setting is reached, LED flashes 5 times. To change direction, hold the power button for 2 sec and immediately release.

Motion Sensor Technology™: Sight sleeps after 5 minutes. Any movement powers up sight to last setting.

Copyright © 2018 Leupold & Stevens, Inc. All rights reserved.

Layout / Design llando88@gmail.com 2022. Unlimited copy and distribution permitted. **REV 10**

GENERAL PURPOSE GRID: 1.00"

Leupold DeltaPoint® Pro



2.5 MOA DOT

Battery is **CR2032**. Aiming point flashes 10 times when low battery power is detected.

Open battery cover by pulling back the battery door release latch. Insert battery positive side (+) up.

Screws move point of impact U/D L/R 1 MOA per click

25 yds: 2.5 MOA=0.7" **10 yds:** 2.5 MOA=0.3"

Torque Optic Screws to 25 in-lbs.

Footprint: DeltaPoint Pro / Body Aluminum / Waterproof to 33'

productspecialist@leupold.com www.leupold.com (503) 526-1400

Copyright © 2018 Leupold & Stevens, Inc. All rights reserved.

Instructions: Cut on dotted lines / fold to make a 3x5 "card". Information adapted from OEM sources; not verified nor endorsed. User is advised to verify any content herein with manufacturers documentation.

ZEROING AID GRID: 2.5 MOA@25 YD=0.65"