

MRDS QUICK REFERENCE CARD SERIES



## Holosun EPS-RD-2

**Power ON:** Shake or press either brightness button

**Power OFF:** Press "+" and "-" together

Press "+" 3 sec to go from Automatic(\*) -> Manual -> Lockout.  
Automatic adjusts to ambient light.


12 brightness levels (4 NV compatible, 8 daylight)

\*default

Layout/Design llando88@gmail.com 2022. Unlimited copy and distribution permitted. **REV 10.2**

GENERAL PURPOSE GRID: 1.00"

## Holosun EPS-RD-2



Battery is **CR1620 3V**. Reticle blinks if battery is low.

Insert new battery "+" side **DOWN**

**Screws** move center of impact U/D, R/L. **1 Click=1.5 MOA**

**25 yds:** 2 MOA = 0.5" **10 yds:** 2 MOA = 0.2"

Optic screws: T10 6-32x5/16": 15 in-lbs+blue T/L

Tray screw : M2x0.4

Clean with lens cleaner, **NO** alcohol or acetone

Footprint: Holosun "K" Series / 7075 T6 AL / IPX8 Certified

[www.holosun.com](http://www.holosun.com) [warranty@holosun.com](mailto:warranty@holosun.com) (909) 594-2888

Instructions: Cut on dotted lines / fold to make a 3x5 "card". Information adapted from OEM sources; not verified nor endorsed. User is advised to verify any content herein with manufacturers documentation.

ZEROING AID GRID: 2 MOA@25 YD±0.52"

MRDS QUICK REFERENCE CARD SERIES



## Holosun EPS-RD-2

**Power ON:** Shake or press either brightness button

**Power OFF:** Press "+" and "-" together

Press "+" 3 sec to go from Automatic(\*) -> Manual -> Lockout.  
Automatic adjusts to ambient light.

12 brightness levels (4 NV compatible, 8 daylight)

\*default

Layout/Design llando88@gmail.com 2022. Unlimited copy and distribution permitted. **REV 10.2**

GENERAL PURPOSE GRID: 1.00"

## Holosun EPS-RD-2



Battery is **CR1620 3V**. Reticle blinks if battery is low.

Insert new battery "+" side **DOWN**

**Screws** move center of impact U/D, R/L. **1 Click=1.5 MOA**

**25 yds:** 2 MOA = 0.5" **10 yds:** 2 MOA = 0.2"

Optic screws: T10 6-32x5/16": 15 in-lbs+blue T/L

Tray screw : M2x0.4

Clean with lens cleaner, **NO** alcohol or acetone

Footprint: Holosun "K" Series / 7075 T6 AL / IPX8 Certified

[www.holosun.com](http://www.holosun.com) [warranty@holosun.com](mailto:warranty@holosun.com) (909) 594-2888

Instructions: Cut on dotted lines / fold to make a 3x5 "card". Information adapted from OEM sources; not verified nor endorsed. User is advised to verify any content herein with manufacturers documentation.

ZEROING AID GRID: 2 MOA@25 YD±0.52"