



## Holosun 510C

**Power ON:** Shake sight or press either brightness button  
**Power OFF:** Press "+" and "-" simultaneously

Press "-" 3 sec to go from Circle+Dot(\*) -> Dot -> Circle  
 Press "+" 3 sec to go from Automatic(\*) -> Manual -> Lockout  
 10 daylight and 2 NV brightness settings.

**Solar Fail Safe™** provides dual power (solar and internal)

\*default

Layout / Design llando88@gmail.com 2022. Unlimited copy and distribution permitted. **REV 10**

GENERAL PURPOSE GRID: 1.00"



## Holosun 510C

**Power ON:** Shake sight or press either brightness button  
**Power OFF:** Press "+" and "-" simultaneously

Press "-" 3 sec to go from Circle+Dot(\*) -> Dot -> Circle  
 Press "+" 3 sec to go from Automatic(\*) -> Manual -> Lockout  
 10 daylight and 2 NV brightness settings.


**Solar Fail Safe™** provides dual power (solar and internal)

\*default

Layout / Design llando88@gmail.com 2022. Unlimited copy and distribution permitted. **REV 10**

GENERAL PURPOSE GRID: 1.00"

## Holosun 510C



Battery is **CR2032**. Reticle blinks if the battery is low (2.2 V).  
 Remove screws, insert new battery "+" side **DOWN**.

**Screws** move center of impact U/D, R/L. Each click = 1/2 MOA

**25 yds:** 65 MOA=17" 2 MOA=0.5"

**10 yds:** 65 MOA=6.8" 2 MOA=0.2"

Push cam clamp lever down & lock to install. (bolt=5-10 in lbs)

Clean with lens cleaner, **NO** alcohol or acetone


Footprint: RMR / Titanium frame / 1 Meter IPX7 waterproof

[www.holosun.com](http://www.holosun.com) [warranty@holosun.com](mailto:warranty@holosun.com) (909) 594-2888

Instructions: Cut on dotted lines / fold to make a 3x5 "card". Information adapted from OEM sources; not verified nor endorsed. User is advised to verify any content herein with manufacturers documentation.

ZEROING AID GRID: 2 MOA@25 YD=0.52"

## Holosun 510C



Battery is **CR2032**. Reticle blinks if the battery is low (2.2 V).  
 Remove screws, insert new battery "+" side **DOWN**.

**Screws** move center of impact U/D, R/L. Each click = 1/2 MOA

**25 yds:** 65 MOA=17" 2 MOA=0.5"

**10 yds:** 65 MOA=6.8" 2 MOA=0.2"

Push cam clamp lever down & lock to install. (bolt=5-10 in lbs)

Clean with lens cleaner, **NO** alcohol or acetone

Footprint: RMR / Titanium frame / 1 Meter IPX7 waterproof

[www.holosun.com](http://www.holosun.com) [warranty@holosun.com](mailto:warranty@holosun.com) (909) 594-2888

Instructions: Cut on dotted lines / fold to make a 3x5 "card". Information adapted from OEM sources; not verified nor endorsed. User is advised to verify any content herein with manufacturers documentation.

ZEROING AID GRID: 2 MOA@25 YD=0.52"