

MRDS QUICK REFERENCE CARD SERIES



Holosun 507k

Power ON: Shake sight or press either brightness button

Power OFF: Press "+" and "-" simultaneously to turn power and motion sensor off (**Shake Awake™** (*) is disabled)

Press "-" 3 sec, to switch from Circle+Dot(*), Dot, and Circle

Press "+" 3 sec, to switch from Automatic(*) to Manual to Lockout

*default

GENERAL PURPOSE GRID: 1.00"

Layout / Design llando88@gmail.com 2021. Unlimited copy and distribution permitted. **REV 9**

Holosun 507k



10 daylight and 2 NV brightness settings.

Your selected Manual Brightness is ☐ clicks down from FULL BRIGHT. Battery is a **CR1632**. Reticle blinks if the battery is low (2.2 V).

Insert new battery "+" side **DOWN**.

Adjustment screws move center of impact U/D, R/L. 1click = 1MOA

25 yds: 32MOA=8.4" 2MOA=0.5" **10 yds:** 32MOA=3.4" 2MOA=0.2"

Torque Optic Screws to 15 in-lbs using medium/blue threadlocker.

Clean with lens cleaner, **NO** alcohol or acetone

Footprint: Shield*

www.holosun.com warranty@holosun.com (909) 594-2888

ZEROING AID GRID: 2 MOA @ 25 YD=0.52"

Instructions: Cut on dotted lines / fold to make a 3x5 "card". Information adapted from OEM sources; not verified nor endorsed. User is advised to verify any content herein with manufacturers documentation.

MRDS QUICK REFERENCE CARD SERIES



Holosun 507k

Power ON: Shake sight or press either brightness button

Power OFF: Press "+" and "-" simultaneously to turn power and motion sensor off (**Shake Awake™** (*) is disabled)

Press "-" 3 sec, to switch from Circle+Dot(*), Dot, and Circle


Press "+" 3 sec, to switch from Automatic(*) to Manual to Lockout

*default

GENERAL PURPOSE GRID: 1.00"

Layout / Design llando88@gmail.com 2021. Unlimited copy and distribution permitted. **REV 9**

Holosun 507k



10 daylight and 2 NV brightness settings.

Your selected Manual Brightness is ☐ clicks down from FULL BRIGHT. Battery is a **CR1632**. Reticle blinks if the battery is low (2.2 V).

Insert new battery "+" side **DOWN**.

Adjustment screws move center of impact U/D, R/L. 1click = 1MOA

25 yds: 32MOA=8.4" 2MOA=0.5" **10 yds:** 32MOA=3.4" 2MOA=0.2"

Torque Optic Screws to 15 in-lbs using medium/blue threadlocker.

Clean with lens cleaner, **NO** alcohol or acetone

Footprint: Shield*

www.holosun.com warranty@holosun.com (909) 594-2888

ZEROING AID GRID: 2 MOA @ 25 YD=0.52"

Instructions: Cut on dotted lines / fold to make a 3x5 "card". Information adapted from OEM sources; not verified nor endorsed. User is advised to verify any content herein with manufacturers documentation.